

CAM TYPE DOOR LOCKS

No. 7502-UR & 7502-UL

Two-point cam-type lock.
Welded installation shown.

This anti-rack, cam lock has been designed as a system that will allow the greatest flexibility of application. The user has a choice of stamped steel or malleable iron keepers of varying widths, a third-point steel keeper, stamped-steel offset or straight rod guides and supplementary bearing covers and back plates. Thus, the 7500 Series can be adapted for everything from medium-duty applications to the most severe service demands. Any model of the 7500 can be shipped completely welded to your specifications, saving time and money. It can be furnished with the top cam loose if you have more than one length requirement.

For all van bodies, trailers, refrigerated equipment and all types of gasketed doors.

Features:

- Anti-rack cams and keepers.
- Saddle-type construction of the cam ensures a secure weld and permits use of any standard 3/4" tube, eliminating grinding and other on-the-job fitting.
- Rack control in every direction.
- Flush-mount construction.
- Frost-breaking action.

When ordering, give dimensions from center of upper cam to center of lower cam ("A" dimension), and from center of handle to center of lower cam ("C" dimension). If ordering with top cam loose, supply overall length ("B" dimension). Lock will be furnished with cams and handle clip welded. Specify left- or right-hand installation.

Tubing Dimensions:

O.D. — 1.050". Wall thickness — .108"

