

HANDLES – L & T STYLES

TEE HANDLES • Disc Tumbler



1001 Series TEE HANDLE

Disc Tumbler

Can be Masterkeyed
For Metal or Wood Application

Material: Pressure Cast Handle,
Steel Zinc Plated Spindle

Operation: Furnished for one, two,
or three point locking, right or left
hand doors, with 90 or 180 degrees
rotation (90 degrees RH regularly
furnished)

• 90 degree RH handles rotate
counter clockwise from 12 to
9 o'clock



• 90 degree LH handles rotate
clockwise from 12 to 3 o'clock
• 180 degree handles are reversible
for RH or LH doors
Key is removable in locked or
unlocked position for either 90 or
180 degree handles

Cam Positioning: Square spindle
allows cams to be mounted at 12, 3,
6, and 9 o'clock

Rods and Guides: Not furnished
Spindle Length: Regularly furnished
25/32" and 3 1/2" long (measured
from back of escutcheon). Also
available in 1/4" increments from
1" to 3 1/2".

Surface Mounting: In addition to
mounting shown, handles are
available with attaching holes
through face of escutcheon for
surface mounting -1 1/2" c. to c.,
countersunk for #10-32 screws.
When ordering, suffix S to number
(1001S). Screws not furnished.

Rekeying: Plug removal access
hole added to shank of handle
allows for removal of plug assembly
for rekeying purposes. To remove
plug, insert key and rotate 90
degrees. Insert a small tool (e.g.,
paper clip) in access hole and
depress retainer while pulling key
and plug out of handle.




Part Number	Function	Material		Key Changes	Key Blank No.	Masterkeyed Key Changes	Key Blank No.
		Handle	Spindle				
1001	Locking Handle	Pressure Cast	Steel, Zinc Plated	200	5865JVR	180	5860KS
1001A	Operating Handle,	Satin Chrome Finish		700	8658JVR	700	5861KS
1001B	non-locking Rigid Handle, non-operating	US26D					

Part No/Hand	Stock ID No.	MKYD	Spindle Length	US26D	US2G	Stock Qty.	Approx. Boxed Wt. (lbs./ oz.)
1001 - RH KA-CAT45 Tee	02650		25/32"	•		10	5/10
1001 - RH CAT 60 Tee	00588		25/32"	•		10	5/10
1001 - RH KA-CAT45 Tee	02655		3 1/2"	•		10	5/10
1001 - RH CAT 60 Tee	02370		3 1/2"	•		10	5/10
1001 - RH or LH		2.23	X	•			
1001A - RH Tee Non-locking	00589		25/32"	•		10	5/10
1001A - RH Tee Non-locking	02367		3 1/2"	•		10	5/10
1001A Non-locking		-	X	•			
1001AS Surface non-locking			X	•			
1001B Non-locking rigid*				•			
1001S		2.23	X	•			
H1-US2G	00074				•		
H1					•		
H2-US2G	00075				•		
H2					•		
H3-US2G	00076				•		
H3					•		
S14441					•		
S14452					•		


* Minimum order 500 pieces

X = Spindle for metal applications standard length is 25/32". Other lengths available 1" up to 3 1/2", at additional cost.

CAMS FOR USE ON BOTH THE 1000 AND 1001




Cam No. S14441
Wrought Steel Zinc Plated



Cam No. S14452
Wrought Steel Zinc Plated

For use with 1000 & 1001 handle ONLY. For use with locking devices or handles having 0.314/0.317 spindle on the square.



Mounting Hole
Locations for
1000/1001