
HANDLES - L & T STYLES



Mounting holes at 44mm centres are totally hidden when handle is locked


ORDERING CODE


9/01280	'Titan' (160mm) locking, black
9/01280/01	As above, FT111
9/01279	'Titan' (160mm), non-locking, black



Handles operate through 180° as standard (non-handed). Rotation can be limited to 90° LH (clockwise) or 90° RH (anticlockwise), or to special order, to 180° horizontal movement as shown. Handles will lock in each 90° position.

SPECIFICATION





A.	Handle length	160mn
В.	Mounting width	37mm
C.	Face height	41mn
	Depth of handle boss	
	Shaft length	
	Clearance	
G.	Hole centres	44mn
Η.	Hole sizes (open) dia	5.5mm c/s 10mn

'TITAN' SERIES HEAVY-DUTY HANDLES 160mm LENGTH

Created to provide a robust, modern design, the 'Titan' series is much stronger than normal handles. In particular, metal section at the base of the handle casting is more than twice usual thickness, preventing fracture and resisting lateral loads.

Large size, wide section for good grip, convenience of external mounting but with screws fully concealed when locked, double-sided keys as standard.

180° as standard, rotation can be limited to 90°, LH/RH, or to the special '180° horizontal' option. Handles lock at each 90° position.

Fix through countersunk holes at 44mm centres, which are completely hidden when handle is locked. Neoprene gasket supplied.

'FT' double-sided keys as standard with 'shuttered' keyway. Alternatively 'FS', or 'DLP' key types.

Black as standard, other finishes to special order only.

- Shaft lengths
- Threaded shafts (M10)
- Special key numbers/sets
- 90° LH/RH rotation