

HANDLES – L & T STYLES

LEVER 'L' HANDLES WITH SURFACE MOUNTING

'FT' Keys
Optional



Single-sided 'FS'
keys are standard



Good-looking handles with rectangular, surface-mounted escutcheons for either open- or concealed-fixing. Lock cylinders are "shuttered" for weather-resistance and there is choice of 38mm (1.5 inch) or 44mm (1.75 inch) hole centres.

180° as standard, rotation can be limited to 90°, LH/RH, or 360° free-movement.

Fix through countersunk holes, or with concealed-fixing models use screws provided (M4 x 8mm) to secure from beneath. Neoprene gasket provided.



'FS' keys as standard with 'shuttered' keyway optionally 'FT' or 'DLP' key types.

Chromium plated or black powder-coated.

ORDERING CODE


With 38 mm open-fixing	
9/00167	Lever 'L', locking, chrome
9/00167/01	As above, FS 880 keys
9/00170	Lever 'L', non-locking, chrome
With 38 mm concealed-fixing	
9/00171	Lever 'L', locking, chrome
9/00171/01	As above, FS 880
9/00172	Lever 'L', non-locking, chrome
With 44 mm open-fixing	
9/00173	Lever 'L', locking, chrome
9/00173/01	As above, FS 880
9/00183	Lever 'L', non-locking, chrome

SPECIFICATION



- Shaft lengths
- Threaded shafts (M10)
- Special key numbers/sets
- 90° LH/RH rotation
- Spring-return, LH/RH

Use with latching cams, slam latches or rod systems.



Handles operate through 180° as standard (non-handed). To special order, rotation can be limited to 90° LH (clockwise) or 90° RH (anticlockwise). Handles will lock at each 90° position.

A.	Handle length.....	115mm
B.	Mounting width.....	33mm
C.	Face height.....	42mm
D.	Depth of handle boss.....	10mm
E.	Shaft length.....	125mm
F.	Diameter of boss.....	14mm
G.	Hole centres.....	38/44mm
H.	Hole sizes (open) dia.....	5mm, c/s 9mm

Industrial Hardware Distributors, Inc.

620 Spicer St., Akron, OH 44311 • 800.824.1864 | 3415 S.W. 6th St., Ocala, FL 34474 • 800.682.8900
www.industrialhwe.com